

Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 1/15

P.A. 103 COMP. B

Safety Data Sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

P.A. 103 COMPONENT B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Not available

1.3. Details of the supplier of the safety data sheet

Name Full address District and Country SINIT INTERMAR S.r.I. Via V. Chiarugi, 76/t 45100 Rovigo (Italy) tel. ++39 0425 361961 fax ++39 0425 410115

e-mail address of the competent person responsible for the Safety Data Sheet Product distribution by: info@sinitworks.com Cesare Giovannoni

1.4. Emergency telephone number

For urgent inquiries refer to

+39 0425 361961

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, category 2	H361	Suspected of damaging fertility or the unborn child.
Acute toxicity, category 4	H302	Harmful if swallowed.
Acute toxicity, category 4	H332	Harmful if inhaled.
Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity,	H412	Harmful to aquatic life with long lasting effects.
category 3		

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



P.A. 103 COMP. B

Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 2/15

Hazard pictograms:







Signal words:

Danger

Hazard statements:

H361 Suspected of damaging fertility or the unborn child.

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsina.

Contains: PARATERZIARIOBUTILFENOLO

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

ADDOTTO DI IPDA

TALC

Product not intended for uses provided for by Dir. 2004/42/CE.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

CALCIUM CARBONATE

CAS 471-34-1 $19 \le x < 24$

EC 207-439-9



P.A. 103 COMP. B

Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 3/15

INDEX -

TALC

CAS 14807-96-6 15 ≤ x < 20 Acute Tox. 4 H332, STOT SE 3 H335

EC 238-877-9

INDEX -

ADDOTTO DI IPDA

CAS 38294-64-3 14 ≤ x < 19 Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1

H318, Skin Sens. 1 H317, Aquatic Chronic 3 H412

EC 500-101-4

INDEX -

BENZYL ALCOHOL

CAS 100-51-6 14 ≤ x < 19 Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319

EC 202-859-9

INDEX 603-057-00-5

BARIO SOLFATO

CAS 7727-43-7 $9 \le x < 14$

EC 231-784-4

INDEX -

Reg. no. 01-2119491274-35-xxxx

3-AMINOMETHYL 3,5,5-

TRIMETHYLCYCLOHEXYLAMINE

CAS 2855-13-2 7 ≤ x < 8 Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1

H318, Skin Sens. 1 H317, Aquatic Chronic 3 H412

EC 220-666-8

INDEX 612-067-00-9

PARATERZIARIOBUTILFENOLO

CAS 98-54-4 $4 \le x < 5$ Repr. 2 H361, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335,

Aquatic Chronic 2 H411

EC 202-679-0 INDEX -

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available



P.A. 103 COMP. B

Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 4/15

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.



Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 5/15

P.A. 103 COMP. B

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

ESP

España

INSHT - Límites de exposición profesional para agentes químicos en España 2017

GBR

United Kingdom

EH40/2005 Workplace exposure limits

SVN

Slovenija TLV-ACGIH Uradni list Republike Slovenije 04.06.2015 (1602) - Pravilnik o spremembah in dopolnitvah Pravilnika o

varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu

ACGIH 2017

CALCIUM CARBONA

Threshold Limit Value						
Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
WEI	CDD	1				

Threshold Limit Value							
Туре	Country	TWA/8h		STEL/15min			
		mg/m3	ppm	mg/m3	ppm		
VLA	ESP	2					
WEL	GBR	1					
MV	SVN	2				RESP	
TLV-ACGIH		2					

BENZYL ALCOHOL

Predicted no-effect concentration - PNEC			
Normal value in fresh water	1	mg/l	
Normal value in marine water	1	mg/l	
Normal value for fresh water sediment	527	mg/kg/d	
Normal value for marine water sediment	527	mg/kg/d	
Normal value of STP microorganisms	39	mg/l	
Normal value for the terrestrial compartment	456	mg/kg/d	

Health - Derived no-effect level - DNEL / DMEL

Effects on	Effects or
consumers	workers



DADIO COL EATO

SINIT INTERMAR S.R.L.

Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 6/15

	P.A	۱. 10)3 (CO	MΡ). B
--	-----	-------	------	----	----	------

Route of exposure	Acute local	Acute systemic		Chronic systemic	Chronic local		Chronic systemic
Oral			20 mg/kg bw/d	4 mg/kg/d			
Inhalation			110 mg/m3	22 mg/m3			
Skin			20 mg/kg/d			40 mg/kg/d	8 mg/kg/d

Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		10				
Predicted no-effect cond	centration - PNEC					
Normal value in fresh wa	ater			227,8	mg/l	
Normal value for fresh w	ater sediment			7927	mg/kg	
Normal value of STP mi	croorganisms			50,1	mg/l	
Normal value for the terr	restrial compartment			2077	mg/kg/d	

Health - Derived no-eff	fect level - DNEL / [DMEL					
	Effects on				Effects on		
	consumers				workers		
Route of exposure	Acute local	Acute systemic		Chronic	Chronic local		Chronic
				systemic			systemic
Oral						VND	13000
							mg/kg/d
Inhalation			VND	10 mg/m3		10 mg/m3	VND

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMIN	NE		
Predicted no-effect concentration - PNEC			
Normal value in fresh water	6	mg/l	
Normal value in marine water	6	mg/l	
Normal value for fresh water sediment	5784	mg/kg	
Normal value for marine water sediment	578	mg/kg	
Normal value of STP microorganisms	318	mg/l	
Normal value for the terrestrial compartment	1121	mg/kg	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.



Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 7/15

P.A. 103 COMP. B

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Fluid mixture Colour grev Odour characteristic Odour threshold Not available Not available Melting point / freezing point Initial boiling point Not available Boiling range Not available > 60 °C Flash point Evaporation Rate Not available Flammability of solids and gases Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Not available Relative density Solubility insoluble Partition coefficient: n-octanol/water Not available Not available Auto-ignition temperature Decomposition temperature Not available Not available Viscosity Explosive properties Not available Oxidising properties Not available

9.2. Other information

Information not available



P.A. 103 COMP. B

Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 8/15

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

CALCIUM CARBONATE

Decomposes at temperatures above 800°C/1472°F.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

May react dangerously with: strong oxidising agents, concentrated inorganic acids.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

BENZYL ALCOHOL

Avoid exposure to: air, sources of heat, naked flames.

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Avoid contact with: strong acids, strong oxidants.

10.5. Incompatible materials

CALCIUM CARBONATE

Incompatible with: acids.

BENZYL ALCOHOL

Incompatible with: sulphuric acid,oxidising substances,aluminium.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

CALCIUM CARBONATE

May develop: calcium oxides,carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using



Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 9/15

P.A. 103 COMP. B

the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation - mists / powders) of the mixture:
Acute Tox. 4
LC50 (Inhalation - vapours) of the mixture:
Acute Tox. 4

Acute Tox. 4 LD50 (Oral) of the mixture:

1633,61 mg/kg

LD50 (Dermal) of the mixture:

>2000 mg/kg

PARATERZIARIOBUTILFENOLO

LD50 (Oral) > 2000 mg/kg rat

CALCIUM CARBONATE

LD50 (Oral) 6450 mg/kg Rat

BENZYL ALCOHOL

LD50 (Oral) 1230 mg/kg Rat

LD50 (Dermal) 2000 mg/kg Rabbit

LC50 (Inhalation) > 4,1 mg/l/4h Rat

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

LD50 (Oral) 1030 mg/kg



Revision nr. 3 Dated 01/10/2018

Printed on 01/10/2018

Page n. 10/15

P.A. 103 COMP. B

BARIO SOLFATO

LD50 (Oral) > 5000 mg/kg rat

LD50 (Dermal) > 2000 mg/kg rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Suspected of damaging fertility or the unborn child

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment. **12.1. Toxicity**

PARATERZIARIOBUTILFENOLO



P.A. 103 COMP. B

Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 11/15

LC50 - for Fish > 1 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea 4,8 mg/l/48h Daphnia EC50 - for Algae / Aquatic Plants 1,6 mg/l/72h Pesci

BENZYL ALCOHOL

LC50 - for Fish 460 mg/l/96h Pimephales promelas EC50 - for Crustacea 230 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 700 mg/l/72h Pseudokirchnella subcpitata

3-AMINOMETHYL 3,5,5-

TRIMETHYLCYCLOHEXYLAMINE

LC50 - for Fish110 mg/l/96h Leuciscus idusEC50 - for Crustacea43 mg/l/48h daphnia magna

EC50 - for Algae / Aquatic Plants > 50 mg/l/72h Desmodesmus subspicatus

BARIO SOLFATO

LC50 - for Fish > 3,5 mg/l/96h Danio rerio
EC50 - for Crustacea 14,5 mg/l/48h daphnia magna

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h Pseudokirchneriella subcapitata

12.2. Persistence and degradability

CALCIUM CARBONATE

Solubility in water 0,1 - 100 mg/l

TALC

Solubility in water < 0,1 mg/l

BENZYL ALCOHOL Rapidly degradable

3-AMINOMETHYL 3,5,5-

NOT rapidly degradable

TRIMETHYLCYCLOHEXYLAMINE

Solubility in water

1000 - 10000 mg/l

12.3. Bioaccumulative potential

BENZYL ALCOHOL

Partition coefficient: n-octanol/water 1,1

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.



P.A. 103 COMP. B

Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 12/15

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, 3

IATA:

3267

14.2. UN proper shipping name

ADR / RID: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (ADDOTTO DI IPDA ; 3-AMINOMETHYL 3,5,5-

TRIMETHYLCYCLOHEXYLAMINE)

IMDG: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (ADDOTTO DI IPDA; 3-AMINOMETHYL 3,5,5-

TRIMETHYLCYCLOHEXYLAMINE)

IATA: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (ADDOTTO DI IPDA ; 3-AMINOMETHYL 3,5,5-

TRIMETHYLCYCLOHEXYLAMINE)

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8



14.4. Packing group

ADR / RID, IMDG, II

IATA:

14.5. Environmental hazards

ADR / RID: NO IMDG: NO



P.A. 103 COMP. B

Revision nr. 3 Dated 01/10/2018

Printed on 01/10/2018

Page n. 13/15

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 80 Limited

Quantities: 1 restriction code: (E)

Tunnel

Packaging

instructions:

Special Provision: -

IMDG: EMS: F-A, S-B Limited

Cargo:

Pass.:

Quantities: 1

Maximum

quantity: 30 L

855 Maximum Packaging

instructions: quantity: 1 L

851

Special Instructions: A3, A803

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

IATA:

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>

3 Point

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None



Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018
Page n. 14/15

P.A. 103 COMP. B

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 2 Reproductive toxicity, category 2

Acute Tox. 4 Acute toxicity, category 4

Skin Corr. 1B Skin corrosion, category 1B

Eye Dam. 1 Serious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1 Skin sensitization, category 1

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H361 Suspected of damaging fertility or the unborn child.

H302+H332 Harmful if swallowed or if inhaled.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- · IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP



Revision nr. 3

Dated 01/10/2018

Printed on 01/10/2018

Page n. 15/15

P.A. 103 COMP. B

- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.